

Page 1/8

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 10.04.2017 Revision: 10.04.2017

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: Kapci 6033
- · Article number: 6033
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture .
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kapci Coatings

Industrial Zone El - Raswa

Port Said

EGYPT

info@kapci.com

- · Further information obtainable from: Product safety department
- · Emergency telephone number: During normal opening times: +20 66 3770000

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

 The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms





GHS02

GHS07

· Signal word Warning

(Contd. on page 2)

Printing date 10.04.2017 Revision: 10.04.2017

Trade name: Kapci 6033

(Contd. of page 1)

· Hazard-determining components of labelling:

n-butyl acetate

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

ſ	· Dangerous components:		
		,	10-25%
	EINECS: 215-535-7	🏇 Flam. Liq. 3, H226; 🚯 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
			10-25%
	EINECS: 204-658-1	🍅 Flam. Liq. 3, H226; փ STOT SE 3, H336	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Printing date 10.04.2017 Revision: 10.04.2017

Trade name: Kapci 6033

(Contd. of page 2)

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- \cdot *Specific end use*(s) *No further relevant information available.*

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

· Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

(Contd. on page 4)

Printing date 10.04.2017 Revision: 10.04.2017

Trade name: Kapci 6033

(Contd. of page 3)

· Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

(Contd. on page 5)

Printing date 10.04.2017 Revision: 10.04.2017

Trade name: Kapci 6033

	(Contd. of page
Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. : 124 °C
Flash point:	27 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	370 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
Vapour pressure at 20 °C:	10.7 hPa
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	50.0 %
VOC (EC)	50.00 %
Solids content:	50.0 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:	
1330-20-7 xylene	
Oral LD50 4300 mg/kg (rat)	

(Contd. on page 6)

(Contd. of page 5)

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 10.04.2017 Revision: 10.04.2017

Trade name: Kapci 6033

Dermal LD50 2000 mg/kg (rabbit)

· Primary irritant effect:

· Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

1 4 0	n .		C	
141	ransport	T M	orma	tion

· UN-Numbe	ľ
------------	---

· ADR, IMDG, IATA UN1263

· UN proper shipping name

· ADR 1263 PAINT · IMDG, IATA PAINT

(Contd. on page 7)

Printing date 10.04.2017 Revision: 10.04.2017

Trade name: Kapci 6033

	(Contd. of page
Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
Packing group ADR, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	<i>F-E,<u>S-E</u></i>
Stowage Category	A
Transport in bulk according to Annex II of	
and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
The second section of the second	Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	3 D/E
1 unnet restriction code	υ/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

(Contd. on page 8)

Printing date 10.04.2017 Revision: 10.04.2017

Trade name: Kapci 6033

(Contd. of page 7)

H315 Causes skin irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Quality Assurance & Environment Departement
- · Contact: Chemist / Mohamed Khalil
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

GB